

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/095770 A1

(51) International Patent Classification⁷: **F02B 23/00**,
53/04

(21) International Application Number:
PCT/CA2005/000462

(22) International Filing Date: 30 March 2005 (30.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2,464,227 31 March 2004 (31.03.2004) CA

(71) Applicant and

(72) Inventor: **MAJOR, Jean-Louis** [CA/CA]; 5768 9th Line,
R.R.#2, Hornby, Ontario L0P 1E0 (CA).

(74) Agent: **CARSON, James, W.**; Blaney McMurtry LLP, 2
Queen Street East, Suite 1500, Toronto, Ontario M5C 3G5
(CA).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: DOUBLE ACTION PISTON ASSEMBLY



(57) Abstract: The present invention relates to a double action piston assembly for an internal combustion engine. The assembly comprises a combustion chamber (11) in axial alignment with a compression chamber (29) and in perpendicular alignment with a crankshaft (31). A connecting rod (44) has a first end connected to the crankshaft and a second end connected to a central power rod (8) itself connecting the compression piston (27) and the combustion piston (6). The central power rod traverse the compression and combustion chambers in their longitudinal axis. The combustion and compression chambers further include upper and lower inlet and outlet ports (12, 14, 34, 37, 13, 15, 35 and 38). The upper outlet port of the compression chamber is connected to the lower intake port of the combustion chamber and vice-verca. The upper and lower inlet ports of the compression chamber comprise means to introduce water vapour (40, 41) into the compression chamber.

WO 2005/095770 A1